

RPS

Stackable Paving Support Pad

Overview

The RPS Stackable Paving Support Pad is a stackable paving support pedestal that is simple to install. Designed for use on totally flat surfaces, this support is a very economical way to create a clear space below paving, allowing for rapid water drainage.

- Spacer tabs create a perfectly uniform gap between slabs
- Drainage holes ensure fast and efficient rainwater drainage
- Supports can be stacked to the desired height – up to 6 high for the RPS range, up to 10 high for the RPS-HD range
- Supports can be snapped into halves or quarters for supporting slabs at edges or corners
- Suitable for all calibrated paving types, including porcelain, concrete, and natural stone



Details

Material	Polypropylene (recyclable)
Dimensions	See “Part information” below
Spacer tab thickness	4mm
Height range	See “Part information” below

Performance



Reaction to fire (BS EN 13501-5)	B _{ROOF} (t4)
Compressive strength	See “Compatible System” data
Biological and chemical	Resistant to moulds, algae, alkali, bitumen, UV
Warranty	10 years*

*when used as part of a complete RYNO system

Part information

Part code	Height	Diameter	Pack quantity
RPS-10	10mm	145mm	250
RPS-15	15mm	145mm	250
RPS-1	1mm	145mm	1000
RPS-2	2mm	145mm	1000
RPS-3	3mm	145mm	1000
RPS-HD15	15mm	170mm	200
RPS-HD2	2mm	170mm	500

Compatible components

	<p>BRSP Base Rubber Shock Pad</p>		<p>CP-AD Adira Concrete Paver</p>
---	--	--	--

Compatible systems

TerraSmart®
Pedestal Paving System

Straightforward, robust paving system for waterproofed substrates, **where non-combustibility isn't required**

Got questions? Give us a shout.

Visit www.rynosystems.com or call us today on **+44 (0)203 967 3500** or reach out on sales@rynosystems.com