PHYSICAL TESTING REPORT



Ryno Ltd Castlepoint Castle Way Ellon

Aberdeenshire AB41 9RG

FAO: Mr. Amos Whiteside

Report of Tests on: TerraSmart Deck: Vitrified Composite decking **Your Reference:** TerraSmart Deck: Vitrified Composite decking

Lucideon Reference: UK232010-13789/CR1

Date Reported: 23-Jun-2023 Order Number: Proforma Invoice

Date Logged: 31-May-2023 **Date(s) of Test(s):** 20-Jun-2023 **to** 20-Jun-2023

Determination of Modulus of Rupture

BSENISO 10545-4: 2019

	Thickness	Breaking Strength	Load	Modulus of Rupture
No.	mm	N	N	N/mm²
1	25.97	12133	7042	27.0
2	25.94	8975	5209	20.0
3	25.94	11727	6714	26.1
4	25.93	10691	6205	23.9
5	25.95	8981	5177	20.0
6	25.95	8830	5090	19.7
7	25.90	9238	5253	20.7

Sampling Procedure: None

Description of Test Specimen(s): Vitrified Composite Decking

Thickness of Rubber: 5 mm Diameter of Rod: 20 mm

Overlap: 10 mm Span: 255 mm

Average Modulus of Rupture Value: 22.5 N/mm² Average Breaking Strength Value: 10082 N

Richard Oliver 01782 764407 mohammad.malik@uk.lucideon.com

End of Test Report



This Report supersedes the report dated 14/06/2023 UK232010 MOR. Re-Issued following clarification at clients request.

Manager

This report is issued in accordance with the Conditions of Business of Lucideon Limited and relates only to the sample(s) tested. No responsibility is taken for the accuracy of the sampling unless this is done under our own supervision. This report shall not be

reproduced in part without the written approval of Lucideon Limited, nor used in any way as to lead to misrepresentation

Lucideon Limited Queens Road, Penkhull Stoke-on-Trent

Staffordshire ST4 7LQ

Page 1 of 1