

BBS

Baseboard Screw



Overview

The Baseboard Screw features a self-tapping tip and partial thread designed to securely grip the fastening surface whilst fixing down Baseboards, perfect for where the head of the screw is engage with a separate surface to the fixing point. This robust self-drilling countersunk torx screw is crafted from high-grade A2 stainless steel, ensuring exceptional durability and lasting resistance to corrosion.

- Wide thread for secure connection
- A2 stainless steel
- Perfect for Baseboard



Details

Material	Stainless Steel A2
Dimensions	Thread Size 4.5mm Thread length 24mm Overall length 40mm
Drive type	Torx T20
Weight	0.34kg/100

Performance

Reaction to fire (BS EN 13501-1)	Inherently A1 (Decision 94-611/EC)

Compatible Components



Got questions? Give us a shout.

Visit www.rynosystems.com or call us today on +44 (0)203 967 3500 or reach out on sales@rynosystems.com



Compatible Systems



TerraSmart®

Rail Paving System

Premium, versatile paving system for waterproofed substrates

TerraSmart®

Ledge Bespoke Planter System

For designs featuring straights and angled corner details

TerraSmart®

Contour Bespoke Planter System

For designs featuring waves, curves, and radiances

TerraSmart®

Ascent Bespoke Planter System

Featuring a backward slant on the planter face

TerraSmart®

Resin Bound Gravel System

Raised, lightweight flooring system with a seamless resin bound aggregate finish.

Got questions? Give us a shout.

Visit www.rynosystems.com or call us today on +44 (0)203 967 3500 or reach out on sales@rynosystems.com