

PSR

Rail Paving Spacer

Patent Number: GB 2581209

Overview

The Rail Paving Spacer is a compatible spacer for the RST Aluminium Paving Support Rail, available in various sizes with T, straight, and cross configurations to accommodate different paving layouts. This robust black plastic spacer features an innovative twist-lock base that slots neatly into the RST rail for seamless and satisfying installation.

- Compatible with RST Aluminium Paving Support Rail
- 4mm spacers as standard
- 2, 3, 5 and 6mm available
- T, straight, and cross configurations
- Twist-lock base for easy installation





Details

| | |
|-----------------------------|------------------------------|
| Material | Polypropylene |
| Colour | Black |
| Spacer tab thickness | See “Part information” below |

Part Information

| Part number | Description | Supplied | Pack quantity |
|-------------|---------------------|-------------|---------------|
| 54.1050 | 2mm Cross Spacer | On request | 25 |
| 54.1052 | 2mm T Spacer | On request | 25 |
| 54.1054 | 2mm Straight Spacer | On request | 25 |
| 54.1061 | 3mm Cross Spacer | On request | 25 |
| 54.1062 | 3mm T Spacer | On request | 25 |
| 54.1063 | 3mm Straight Spacer | On request | 25 |
| 54.1051 | 4mm Cross Spacer | As standard | 25 |
| 54.1053 | 4mm T Spacer | As standard | 25 |
| 54.1055 | 4mm Straight Spacer | As standard | 25 |
| 54.1076 | 5mm Cross Spacer | On request | 25 |
| 54.1077 | 5mm T Spacer | On request | 25 |
| 54.1078 | 5mm Straight Spacer | On request | 25 |
| 54.1079 | 6mm Cross Spacer | On request | 25 |
| 54.1080 | 6mm T Spacer | On request | 25 |
| 54.1081 | 6mm Straight Spacer | On request | 25 |

Compatible systems

| | | |
|---|--|---|
|  BalcaSmart [®] Rail Paving System Premium, versatile paving system for metal framed balconies |  TerraSmart [®] Rail Paving System Premium, versatile paving system for waterproofed substrates | TerraSmart [®] Rail Paving System Premium, versatile paving system for waterproofed substrates, where non-combustibility isn't required |
|---|--|---|

Got questions?

Speak to one of our expert advisors

Visit www.rynogroup.co.uk or call us today on **+44 (0)203 967 3500** or reach out on sales@rynogroup.co.uk.