Report Number: SP4466N





TEST REPORT

Surface Performance Ltd Unit 16 Vicarage Farm Sunbury On Thames London TW16 6DW

0208 2465562 info@surfaceperformance.com www.surfaceperformance.com

BS 7976:2002 + A1:2013 Slip Resistance Testing (Laboratory) Performed on a Sample of:

Fossil Buff Sandstone Setts Tumbled

FOR:

Ryno Group Ltd

- This report has been prepared by Surface Performance Ltd with all reasonable care, skill and diligence within the terms of the contract with the client. This report is not to be reproduced except in full without prior approval.
- This report is confidential to the client and Surface Performance Ltd accept no responsibility towards any third parties to whom this report is made available to. Any such party relies upon this report at their own risk.
- This report shall not be used for contractual purposes unless signed by the Laboratory or Technical Manager.
- The results given in this report are representative of the sample received only.



Report Number: SP4466N

Sample: Fossil Buff Sandstone Setts Tumbled



Surface Performance Ltd Unit 16 Vicarage Farm Sunbury On Thames London TW16 6DW

0208 2465562 info@surfaceperformance.com www.surfaceperformance.com

Approval Sheet & Preface Page 1 Summary of Testing Page 2 Introduction Page 3 Methods Page 3 Location Plans Page 4 Test Results Page 5 Site Photographs Page 6 End of Report Page 7

2.0 SUMMARY OF TESTING

2.1 Testing was performed in accordance with BS 7976:2002 + A1:2013.

2.2 Classification limits are taken from The HSE 2012 publication "Assessing the slip resistance of flooring." (<u>www.hse.gov.uk/pubns/geis2.pdf</u>) and are outside the scope of accreditation.











Report Number: SP4466N

3.0 INTRODUCTION



Surface Performance Ltd Unit 16 Vicarage Farm Sunbury On Thames London TW16 6DW

0208 2465562 info@surfaceperformance.com www.surfaceperformance.com

Surface Performance Ltd carried out slip testing on Monday 24th February 2025 to a Fossil Buff Sandstone Setts Tumbled sample provided for testing by Ryno Group Ltd.

The sample was supplied by the client and received at the laboratory on Monday 17th February 2025 and identified with Surface Performance Ltd sample number SP4466N. The samples are tested as received and the results apply only to the samples tested.

The sample was conditioned for a minimum 24 hours prior to testing at an ambient air temperature of 21-25°C and 40-60% relative humidity in accordance with ISO 291 Class 2 (non tropical countries).

4.0 METHOD

Testing was performed in accordance with BS 7976:2002 + A1:2013 and undertaken using a calibrated pendulum slip tester using Slider 96 & 55.

Testing was carried out at 1 x Location, in 2 directions in both wet & dry conditions.











Report Number: SP4466N



Surface Performance Ltd Unit 16 Vicarage Farm Sunbury On Thames London TW16 6DW

0208 2465562 info@surfaceperformance.com www.surfaceperformance.com

5.0 REQUIREMENTS - HSE 2012 Assessing the Slip Resistance of Flooring.

CLASSIFICATION	PTV RESULT
High Slip Potential	0 - 24
Moderate Slip Potential	25 - 35
Low Slip Potential	36 +

6.0 LOCATION PLAN

6.1 TEST LOCATION PROXIMITY PLAN

The diagram below identifies the test directions on the sample provided.



A ← B











Report Number: SP4466N



Surface Performance Ltd Unit 16 Vicarage Farm Sunbury On Thames London TW16 6DW

0208 2465562 info@surfaceperformance.com www.surfaceperformance.com

<u>7.0 TEST RESULTS</u> (Mean of 4,5,6,7,8 as per BS 7976-2) **SLIDER 96 DRY DIRECTIONS: CLASSIFICATION - LOW SLIP POTENTIAL**

SURFACE TEMP (°C) 21.7				AIR TEMP (°C) 23.2					
Test Direction	Pendulum Swing 1	Pendulum Swing 2	Pendulum Swing 3	Pendulum Swing 4	Pendulum Swing 5	Pendulum Swing 6	Pendulum Swing 7	Pendulum Swing 8	Mean Result
Α	68	68	68	70	70	70	70	70	70
В	71	71	69	69	69	68	70	70	69

SLIDER 96 WET DIRECTIONS: CLASSIFICATION - LOW SLIP POTENTIAL

Test Direction	Pendulum Swing 1	Pendulum Swing 2	Pendulum Swing 3	Pendulum Swing 4	Pendulum Swing 5	Pendulum Swing 6	Pendulum Swing 7	Pendulum Swing 8	Mean Result
A	60	60	61	60	61	61	60	60	60
В	62	62	61	60	60	60	60	60	60

SLIDER 55 DRY DIRECTIONS: CLASSIFICATION - LOW SLIP POTENTIAL

SURFACE TEMP (°C) 21.7					AIR TEMP (°C) 23.2				
Test Pendulum Pendulum Pendulum Pendulum Direction Swing 1 Swing 2 Swing 3 Swing 4				Pendulum Swing 5	Pendulum Swing 6	Pendulum Swing 7	Pendulum Swing 8	Mean Result	
Α	94	94	94	95	95	95	95	95	95
В	93	93	93	94	94	94	94	95	94

SLIDER 55 WET DIRECTIONS: CLASSIFICATION - LOW SLIP POTENTIAL

Test Direction	Pendulum Swing 1	Pendulum Swing 2	Pendulum Swing 3	Pendulum Swing 4	Pendulum Swing 5	Pendulum Swing 6	Pendulum Swing 7	Pendulum Swing 8	Mean Result
Α	68	68	68	68	70	70	70	70	70
В	68	68	69	69	69	71	71	70	70











Report Number: SP4466N

Sample: Fossil Buff Sandstone Setts Tumbled



SITE PHOTOGRAPHS

Surface Performance Ltd Unit 16 Vicarage Farm Sunbury On Thames London

TW16 6DW

0208 2465562 info@surfaceperformance.com www.surfaceperformance.com













Report Number: SP4466N



Surface Performance Ltd Unit 16 Vicarage Farm Sunbury On Thames London TW16 6DW

0208 2465562 info@surfaceperformance.com www.surfaceperformance.com

END OF REPORT









